


## SMOOTHFLEXX PU FOOD X-TRA

Food-grade polyether-polyurethane tubing, reinforced with an impact-resistant rigid PVC spiral

- Applications** conveying technology, beverage production & conveying, grain conveying, food production & -conveying, medical devices
- Structure** TPU / Polyether-Polyurethane, transparent, plastic spiral / rigid PVC
- Temperature** -40°C up to 80°C
- Norms** certified according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C, D1, D2, E



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
38	0,80	133	2,00	0,30	0,34300	20	ND35303800N
51	1,00	179	1,50	0,25	0,50400	20	ND35305100N
63	1,00	221	1,50	0,25	0,63000	20	ND35306300N
76	1,00	266	1,50	0,25	0,74200	20	ND35307600N
102	1,00	357	1,30	0,22	0,99300	20	ND35310200N
127	1,00	445	1,30	0,20	1,23600	20	ND35312700N
152	1,00	532	1,00	0,16	1,47900	20	ND35315200N
203	1,20	711	0,70	0,10	1,97500	10	ND35320300K