

S 7 HYP-TEF EL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive

Applications	paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, air extraction
Structure	Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / multi-layer
Temperature	-40°C up to 175°C, short term up to 190°C
Properties	light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive
Norms	TRBS 2153, ATEX 2014/34/EU



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
76	86,00	0,40	45	0,60	0,17	0,00	3	ND76207600B
76	86,00	0,40	45	0,60	0,17	0,00	6	ND76207600G
102	112,00	0,40	60	0,50	0,10	0,00	3	ND76210200B
102	112,00	0,40	60	0,50	0,10	0,00	6	ND76210200G
127	137,00	0,40	75	0,32	0,06	5,05	6	ND76212700G
127	137,00	0,40	75	0,32	0,06	2,53	3	ND76212700B
152	162,00	0,40	90	0,22	0,04	0,00	6	ND76215200G
152	162,00	0,40	90	0,22	0,04	0,00	3	ND76215200B