VACU PU M AGRI MHR

Lightweight and flexible hose made of polyether polyurethane

Applications agriculture, automation technology & robotics, air supply, cable protection, industrial vacuum cleaners

Structure Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PU

Temperature -40°C up to 90°C, short term up to 125°C

Properties light weight, good flexibility, good tensile strength, ultimate elongation, good abrasion resistance, free of halogen & softeners, phthalate-free







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
80	87,00	0,50	80	0,60	0,35	12,85	30	ND42508050N
90	97,00	0,50	90	0,60	0,35	14,45	20	ND42509050N
102	109,00	0,50	102	0,40	0,30	16,40	20	ND42510250N
110	117,00	0,50	130	0,40	0,30	17,68	20	ND42511050N
120	127,00	0,60	150	0,40	0,30	19,28	20	ND42512050N
127	134,00	0,60	180	0,40	0,30	20,16	20	ND42512750N
140	148,00	0,60	185	0,30	0,20	22,16	20	ND42514050N
160	168,00	0,60	195	0,30	0,20	25,26	20	ND42516050N
200	208,00	0,60	250	0,15	0,15	31,54	20	ND42520050N

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026