S 2 VSM EL 7440

Very smooth internal profile hose made of electrically conductive modified TPO



Applications	industrial vacuum cleaners, vacuum cleaner, cleaning, construction machines, extraction systems
Structure	TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix
Temperature	-50°C up to 60°C
Properties	corrugated outside, smooth inside, excellent flexibility, electrically conductive (R ≤ 10^3 Ohm), good flexibility restoring force after compression or bending
Norms	ATEX 2014/34/EU





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
32	40,50	70	0,50	0,50	0,23100		ND40303200P
38	48,00	80	0,40	0,40	0,35500		ND40303800P
50	61,00	120	0,25	0,25	0,46400	25	ND40305000P
60	72,00	140	0,20	0,20	0,63100	25	ND40306000P

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026