Ocono

France

MONOFLEXX SL VERT/NOIR

Flexible PVC hose reinforced with shock resistant rigid PVC spiral



Applications agriculture, pond technology, waste water, irrigation, sewage treatment plants

Structure soft PVC, green, transparent, plastic spiral / rigid PVC

Temperature -5°C up to 60°C

Properties good flexibility, high pressure resistance, high vacuum resistance, very smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
20	25,40	2,70	104	7,00	0,69	0,21000	10,50	50	NA90202065R
25	29,80	2,50	130	7,00	0,69	0,30000	6,25	25	NA90202565P
25	29,80	2,90	130	7,00	0,69	0,30000	12,50	50	NA90202565R
32	38,00	3,00	155	7,00	0,69	0,39000	9,75	25	NA90203265P
32	38,00	3,00	155	7,00	0,69	0,39000	19,50	50	NA90203265R
38	45,00	3,50	180	6,00	0,69	0,47000	13,00	25	NA90203865P
38	45,00	3,50	180	6,00	0,69	0,47000	23,50	50	NA90203865R
50	57,60	4,20	240	5,00	0,69	0,76000	19,00	25	NA90205065P
50	57,60	4,20	240	5,00	0,69	0,76000	38,00	50	NA90205065R

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 25.11.2026