

S 5 PE M

Light weight and flexible spiral hose made of Polyethylene

Applications	extraction systems, extractions arms, printing machines, steam extraction, solvent vapor extraction
Structure	PE, transparent, steel wire / spring steel wire / coated / PP
Temperature	-40°C up to 80°C
Properties	light weight, good flexibility, very good chemical resistance, weather proof, hydrolysis & microbe resistant, free of halogen & softeners



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	30,00	0,50	25	2,35	0,75	1,46	10	ND58302500K
25	30,00	0,50	25	2,35	0,75	2,19	15	ND58302500M
32	37,00	0,50	32	1,90	0,50	1,82	10	ND58303200K
32	37,00	0,50	32	1,90	0,50	2,73	15	ND58303200M
38	43,00	0,50	38	1,85	0,45	2,13	10	ND58303800K
38	43,00	0,50	38	1,85	0,45	3,20	15	ND58303800M
40	45,00	0,50	40	1,80	0,40	2,23	10	ND58304000K
40	45,00	0,50	40	1,80	0,40	3,35	15	ND58304000M
50	56,00	0,50	50	1,50	0,35	4,04	10	ND58305000K
50	56,00	0,50	50	1,50	0,35	6,05	15	ND58305000M
60	66,00	0,50	60	1,35	0,28	4,78	10	ND58306000K
60	66,00	0,50	60	1,35	0,28	7,17	15	ND58306000M
70	76,00	0,50	70	1,00	0,20	5,52	10	ND58307000K
70	76,00	0,50	70	1,00	0,20	8,28	15	ND58307000M
80	86,00	0,50	80	0,80	0,13	6,26	10	ND58308000K
80	86,00	0,50	80	0,80	0,13	9,39	15	ND58308000M