

## GreenX OneFlat L

Light weight flat hose with a PVC double layer and woven polyester yarn inlay

|                     |                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | waste water, construction machines, construction drying, irrigation, cable protection                      |
| <b>Structure</b>    | PVC, blue, opaque                                                                                          |
| <b>Temperature</b>  | -20°C up to 65°C                                                                                           |
| <b>Properties</b>   | light weight, crush-resistant, can be driven over, high pressure resistance, smooth inside, smooth outside |


hydrolysis  
resistant

microbe-  
resistant

flame  
retardant


liquids

| Inner Diameter (mm) | Max. Operating Pressure (bar) | Burst Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|-------------------------------|----------------------|---------------|-----------------------------|------------|----------------|
| 32                  | 4,00                          | 12,00                | 0,17000       | 8,50                        | 50         | NG10003200R    |
| 38                  | 4,00                          | 12,00                | 0,21000       | 10,50                       | 50         | NG10003800R    |
| 40                  | 4,00                          | 12,00                | 0,21000       | 21,00                       | 100        | NG10004000T    |
| 40                  | 4,00                          | 12,00                | 0,21000       | 10,50                       | 50         | NG10004000R    |
| 50                  | 4,00                          | 12,00                | 0,28000       | 28,00                       | 100        | NG10005100T    |