


S 4 SGUIPE

Highly flexible PVC hose with coated spring steel wire

Applications	industrial vacuum cleaners, vacuum cleaner, cleaning, dust extraction, construction drying
Structure	PVC, black, opaque, steel wire / spring steel wire / coated / PVC
Temperature	-10°C up to 70°C, short term up to 90°C
Properties	good flexibility, crush-resistant, good tensile strength, good chemical resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof,



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
25	31,00	0,50	31	1,70	0,40	0,20000	15	ND41102500M
32	38,00	0,50	38	1,50	0,35	0,28000	15	ND41103200M
35	41,00	0,50	41	1,40	0,30	0,31000	15	ND41103500M
38	44,00	0,50	44	1,40	0,30	0,34000	15	ND41103800M
41	47,00	0,50	47	1,40	0,30	0,37000	15	ND41104100M
44	50,00	0,50	55	1,30	0,28	0,38000	15	ND41104400M
51	57,00	0,50	57	1,30	0,28	0,46000	15	ND41105100M
63	69,00	0,50	69	1,00	0,25	0,53000	15	ND41106300M
70	76,00	0,50	76	0,90	0,20	0,58000	10	ND41107000K
80	86,00	0,50	86	0,70	0,18	0,83000	10	ND41108000K
102	108,00	0,50	108	0,60	0,15	1,00000	10	ND41110200K