

VIDASPIR L UV LISIER

Highly flexible PVC hose reinforced with shock resistant rigid PVC spiral

Applications	liquid manure spreading, agriculture, irrigation, waste water
Structure	PVC / soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-25°C up to 60°C
Properties	very good flexibility, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	25,60	3,30	76	7,00	0,59	0,27500	13,75	50	NA10801960R
25	32,00	3,50	100	7,00	0,59	0,36000	18,00	50	NA10802560R
32	39,00	3,50	128	6,00	0,59	0,46500	23,25	50	NA10803260R
38	45,40	3,70	152	4,00	0,59	0,56000	28,00	50	NA10803860R
40	47,40	3,70	160	4,00	0,59	0,63000	31,50	50	NA10804060R
45	52,40	3,70	160	4,00	0,59	0,66000	33,00	50	NA10804560R
50	58,40	4,20	200	4,00	0,59	0,82000	41,00	50	NA10805060R