FLEX ANT

Flexible PVC hose reinforced with an shock-resistant hard PVC spiral and copper wire for grounding

Applications pellet transport, granulate conveying, extraction systems, dosing, screening technology

Structure soft PVC, uncolored, transparent, plastic spiral / rigid PVC, coated strand / copper strand

Temperature -5°C up to 60°C

Properties good flexibility, smooth inside, corrugated outside, good chemical resistance, with copper wire for grounding, phthalate-free







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
38	46,00	4,00	190	6,00	0,59	0,58000	14,50	25	NA11103800P
38	46,00	4,00	190	6,00	0,59	0,58000	29,00	50	NA11103800R
40	48,00	4,00	200	6,00	0,90	0,60000	30,00	50	NA11104000R
50	58,60	4,00	250	5,00	6,00	0,78000	39,00	50	NA11105000R
50,5	59,60	4,00	250	5,00	0,90	0,78000	19,50	25	NA11105000P
70	79,00	4,50	350	4,00	0,90	1,33000	39,90	30	NA11107000Q

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026