MONOFLEXX EXTRA UV

Flexible spiral hose with UV stabilisation, for the agricultural industry and farming

Applications agriculture, waste water, irrigation, liquid manure spreading

Structure soft PVC, uncolored, transparent, plastic spiral / rigid PVC

Temperature -25°C up to 60°C

Properties light weight, high vacuum resistance, very smooth inside, corrugated outside, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
18	24,40	2,70	80	7,00	0,69	0,23000	5,75	25	NA90501805P
25	30,80	2,90	110	7,00	0,69	0,29000	7,25	25	NA90502505P
30	36,20	3,10	130	7,00	0,69	0,35000	8,75	25	NA90503005P
32	38,40	3,20	140	7,00	0,69	0,37000	9,25	25	NA90503205P
32	38,40	3,20	140	7,00	0,69	0,37000	18,50	50	NA90503205R
35	0,00	3,30	150	6,00	0,69	0,42000	10,50	25	NA90503505P
40	48,30	3,50	190	6,00	0,69	0,51000	10,20	20	NA90504005N
40	48,30	3,50	190	6,00	0,69	0,51000	12,75	25	NA90504005P
40	47,00	3,50	190	6,00	0,69	0,51000	25,50	50	NA90504005R
45	52,00	3,50	190	6,00	0,69	0,57000	14,25	25	NA90504505P
51	57,60	3,80	240	5,00	0,69	0,71000	17,75	25	NA90505105P
51	57,60	3,80	240	5,00	0,69	0,71000	35,50	50	NA90505105R
55	62,80	3,90	250	5,00	0,69	0,77000	19,25	25	NA90505505P
60	68,00	4,20	270	5,00	0,69	0,82000	20,50	25	NA90506005P
63	68,00	4,10	270	5,00	0,69	0,87000	21,75	25	NA90506305P

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 17.11.2026