

GERTRESS 20 BARS

- Applications** compressed air, agricultural technology, construction machines, vehicle construction, compressors
- Structure** PVC / soft PVC, black, opaque, cross braid
- Temperature** -20°C up to 65°C
- Properties** , high pressure resistance, , good chemical resistance, good ozone- & UV-resistance, weather proof



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Burst Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|----------------------|---------------|-----------------------------|------------|----------------|
| 6 | 12,40 | 3,20 | 24 | 20,00 | 60,00 | 0,12300 | 6,15 | 50 | NS40000600R |
| 6 | 12,40 | 3,20 | 24 | 20,00 | 60,00 | 0,12300 | 12,30 | 100 | NS40000600T |
| 9 | 15,40 | 3,20 | 36 | 20,00 | 60,00 | 0,15000 | 15,00 | 100 | NS40000900T |
| 9 | 15,40 | 3,20 | 36 | 20,00 | 60,00 | 0,19000 | 9,50 | 50 | NS40000900R |
| 10 | 16,40 | 3,20 | 40 | 20,00 | 60,00 | 0,16250 | 16,25 | 100 | NS40001000T |
| 13 | 21,00 | 4,00 | 52 | 20,00 | 60,00 | 0,26200 | 13,10 | 50 | NS40001300R |
| 13 | 21,00 | 4,00 | 52 | 20,00 | 60,00 | 0,26200 | 26,20 | 100 | NS40001300T |
| 16 | 25,60 | 4,80 | 64 | 20,00 | 60,00 | 0,41200 | 20,60 | 50 | NS40001600R |
| 19 | 28,60 | 4,80 | 76 | 20,00 | 60,00 | 0,43940 | 21,97 | 50 | NS40001900R |