S 2 VSM 7411

Very smooth inside profile hose made of modified TPO

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, dust extraction, sprayers

Structure TPO, black / grey aluminium (similar RAL 9007), profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, crush-resistant, can be driven over, very good chemical resistance, good flexibility restoring force after compression or bending







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
25	33,00	50	0,60	0,60	0,15030		ND40002500P
32	40,50	70	0,50	0,50	0,22900	25	ND40003200P
38	48,00	80	0,40	0,40	0,36230		ND40003800P
50	61,00	120	0,25	0,25	0,51630		ND40005000P
60	72,00	140	0,20	0,20	0,62660		ND40006000P
63	75,00	148	0,19	0,19	0,65457		ND40006300P

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 24.11.2026