Ocono

France

S 5 PE M

Light weight and flexible spiral hose made of Polyethylene

Applications extraction systems, extractions arms, printing machines, steam extraction, solvent vapor extraction

Structure PE, transparent, steel wire / spring steel wire / coated / PP

Temperature -40°C up to 80°C

Properties light weight, good flexibility, very good chemical resistance, weather proof, hydrolysis & microbe resistant, free of halogen & softeners







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	30,00	0,50	25	2,35	0,75	2,19	15	ND58302500M
25	30,00	0,50	25	2,35	0,75	1,46	10	ND58302500K
32	37,00	0,50	32	1,90	0,50	1,82	10	ND58303200K
32	37,00	0,50	32	1,90	0,50	2,73	15	ND58303200M
38	43,00	0,50	38	1,85	0,45	2,13	10	ND58303800K
38	43,00	0,50	38	1,85	0,45	3,20	15	ND58303800M
40	45,00	0,50	40	1,80	0,40	3,35	15	ND58304000M
40	45,00	0,50	40	1,80	0,40	2,23	10	ND58304000K
50	56,00	0,50	50	1,50	0,35	4,04	10	ND58305000K
50	56,00	0,50	50	1,50	0,35	6,05	15	ND58305000M
60	66,00	0,50	60	1,35	0,28	4,78	10	ND58306000K
60	66,00	0,50	60	1,35	0,28	7,17	15	ND58306000M
70	76,00	0,50	70	1,00	0,20	5,52	10	ND58307000K
70	76,00	0,50	70	1,00	0,20	8,28	15	ND58307000M
80	86,00	0,50	80	0,80	0,13	6,26	10	ND58308000K
80	86,00	0,50	80	0,80	0,13	9,39	15	ND58308000M

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 24.11.2026