GERTRESS 20 BARS

Flexible, multi-layer PVC hose with high-tensile polyester yarn reinforcement

Applications compressed air, construction machines, vehicle construction, compressors, waste water

Structure soft PVC, black, opaque, cross braid

Temperature -20°C up to 65°C

Properties , high pressure resistance, , good chemical resistance, good ozone- & UV-resistance, weather proof







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,40	3,20	24	20,00	60,00	0,12300	6,15	50	NS40000600R
6	12,40	3,20	24	20,00	60,00	0,12300	12,30	100	NS40000600T
9	15,40	3,20	36	20,00	60,00	0,19000	9,50	50	NS40000900R
9	15,40	3,20	36	20,00	60,00	0,15000	15,00	100	NS40000900T
10	16,40	3,20	40	20,00	60,00	0,16250	16,25	100	NS40001000T
13	21,00	4,00	52	20,00	60,00	0,26200	13,10	50	NS40001300R
13	21,00	4,00	52	20,00	60,00	0,26200	26,20	100	NS40001300T
16	25,60	4,80	64	20,00	60,00	0,41200	20,60	50	NS40001600R
19	28,60	4,80	76	20,00	60,00	0,43940	21,97	50	NS40001900R

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026