# GERTRESS 40 BARS

Multilayer PVC pressure hose with highly tear-resistant Polyester fabric

**Applications** sprayers, agriculture, compressed air, construction machines, fertilizer spreading

**Structure** soft PVC, blue, opaque, cross braid

**Temperature** -10°C up to 60°C

**Properties** very good flexibility, very high pressure resistance, very good chemical resistance, good resistance to compressed air containing mineral oil, good ozone- & UV-resistance, weather proof









| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Max. Operating Pressure (bar) | Burst Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---|---|---|---|---|---|---|---|---|
| 9 | 16,00 | 3,50 | 40,00 | 120,00 | 0,18000 | 18,00 | 100 | NS20000900T |
| 9 | 16,00 | 3,50 | 40,00 | 120,00 | 0,18000 | 9,00 | 50 | NS20000900R |
| 10 | 17,00 | 3,50 | 40,00 | 120,00 | 0,19000 | 19,00 | 100 | NS20001000T |
| 10 | 17,00 | 3,50 | 40,00 | 120,00 | 0,19000 | 9,50 | 50 | NS20001000T |
| 13 | 21,00 | 4,00 | 40,00 | 120,00 | 0,28000 | 28,00 | 100 | NS20001300T |
| 13 | 21,00 | 4,00 | 40,00 | 120,00 | 0,28000 | 14,00 | 50 | NS20001300R |
| 16 | 25,60 | 4,00 | 40,00 | 120,00 | 0,36500 | 18,25 | 50 | NS20001600R |
| 19 | 28,60 | 4,80 | 40,00 | 120,00 | 0,42500 | 21,25 | 50 | NS20001900R |
| 25 | 35,00 | 5,00 | 40,00 | 120,00 | 0,59500 | 29,75 | 50 | NS20002500R |



Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026