

S 7 HYP PRO

Very light weight and highly flexible clip hose made of Hypalon®

Applications	exhaust gas extraction, extraction systems, automotive engineering, vehicle construction, air extraction
Structure	Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / single-layer
Temperature	-40°C up to 175°C
Properties	light weight, very good flexibility, very good temperature resistance, very good chemical resistance, with external abrasion protection spiral



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
50	62,00	0,40	30	0,85	0,40	0,00	3	ND76305000B
50	62,00	0,40	30	0,85	0,40	0,00	6	ND76305000G
60	72,00	0,40	36	0,78	0,28	0,00	3	ND76306000B
60	72,00	0,40	36	0,78	0,28	0,00	6	ND76306000G
76	88,00	0,40	45	0,60	0,17	2,68	3	ND76307600B
76	88,00	0,40	45	0,60	0,17	5,36	6	ND76307600G
80	92,00	0,40	48	0,58	0,16	0,00	3	ND76308000B
80	92,00	0,40	48	0,58	0,16	0,00	6	ND76308000G
102	114,00	0,40	60	0,50	0,10	4,96	6	ND76310200G
102	114,00	0,40	60	0,50	0,10	2,48	3	ND76310200B
112	124,00	0,40	66	0,40	0,08	0,00	6	ND76311200G
112	124,00	0,40	66	0,40	0,08	0,00	3	ND76311200B
120	132,00	0,40	72	0,35	0,06	0,00	6	ND76312000G
120	132,00	0,40	72	0,35	0,06	0,00	3	ND76312000B
127	139,00	0,40	75	0,32	0,06	6,17	6	ND76312700G
127	139,00	0,40	75	0,32	0,06	3,09	3	ND76312700B
140	152,00	0,40	83	0,25	0,04	0,00	6	ND76314000G
140	152,00	0,40	83	0,25	0,04	0,00	3	ND76314000B
152	164,00	0,40	90	0,22	0,04	3,66	3	ND76315200B
152	164,00	0,40	90	0,22	0,04	7,32	6	ND76315200G
160	172,00	0,40	96	0,21	0,04	0,00	3	ND76316000B
160	172,00	0,40	96	0,21	0,04	0,00	6	ND76316000G

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
180	192,00	0,40	108	0,17	0,03	0,00	3	ND76318000B
180	192,00	0,40	108	0,17	0,03	0,00	6	ND76318000G
203	215,00	0,40	120	0,15	0,02	6,36	3	ND76320300B
203	215,00	0,40	120	0,15	0,02	12,71	6	ND76320300G
228	240,00	0,40	135	0,12	0,01	7,13	3	ND76322800B
228	240,00	0,40	135	0,12	0,01	14,25	6	ND76322800G
254	266,00	0,40	175	0,10	0,01	7,92	3	ND76325400B
254	266,00	0,40	175	0,10	0,01	15,85	6	ND76325400G
305	317,00	0,40	210	0,07	0,01	18,98	6	ND76330500G
305	317,00	0,40	210	0,07	0,01	9,49	3	ND76330500B