

AQUALIFE KTW TPE

TPE drinking water hose, multi-layered

Applications	drinking water, beverage production & conveying
Structure	TPE/E, blue, opaque, cross braid
Temperature	-30°C up to 70°C, short term up to 90°C
Properties	hydrolysis & microbe resistant, weather proof, high pressure resistance, crush-resistant, smooth inside, smooth outside
Norms	DVGW W 270



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
10	15,40	2,50	70	14,00	42,00	0,09000	2,25	25	NS61101000P
10	15,40	2,50	70	14,00	42,00	0,09000	4,50	50	NS61101000R
13	18,80	3,00	70	15,00	45,00	0,14120	3,53	25	NS61101300P
13	18,80	3,00	70	15,00	45,00	0,14100	7,05	50	NS61101300R
19	26,60	4,10	130	15,00	45,00	0,23200	5,80	25	NS61101900P
19	27,20	4,10	130	15,00	45,00	0,23200	11,60	50	NS61101900R
25	34,60	4,80	220	10,00	30,00	0,40700	20,35	50	NS61102500R
25	34,60	4,80	220	10,00	30,00	0,40720	10,18	25	NS61102500P