

S 2 VSM EL 7440

Very smooth internal profile hose made of electrically conductive modified TPO

| | |
|---------------------|--|
| Applications | industrial vacuum cleaners, vacuum cleaner, cleaning, sawing & milling, textile fiber extraction |
| Structure | TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix |
| Temperature | -50°C up to 60°C |
| Properties | corrugated outside, smooth inside, excellent flexibility, electrically conductive ($R \leq 10^8 \text{ Ohm}$), |
| Norms | ATEX 2014/34/EU |



| Inner Diameter (mm) | Outer Diameter (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|-------------------------------|-------------------|---------------|------------|----------------|
| 32 | 40,50 | 70 | 0,50 | 0,50 | 0,23100 | 25 | ND40303200P |
| 38 | 48,00 | 80 | 0,40 | 0,40 | 0,35500 | 25 | ND40303800P |
| 50 | 61,00 | 120 | 0,25 | 0,25 | 0,46400 | 25 | ND40305000P |
| 60 | 72,00 | 140 | 0,20 | 0,20 | 0,63100 | 25 | ND40306000P |