FLEX ANT PU

Flexible spiral hose made of PVC with PU inner layer and copper wire for grounding



Applications pellet transport, granulate conveying, extraction systems, conveying of abrasive media, powder conveying & -coating

Structure soft PVC, uncolored, transparent, plastic spiral / rigid PVC, coated strand / copper strand

Temperature -5°C up to 60°C

Properties good flexibility, very smooth inside, corrugated outside, very good chemical resistance, weather proof, with copper wire for grounding





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	39,00	3,50	171	7,00	0,74	0,52000	15,60	30	NA13003200Q
40	47,80	3,90	190	7,00	0,74	0,63000	18,90	30	NA13004000Q
45	53,00	3,90	212	6,00	0,69	0,67000	20,10	30	NA13004500Q
51	58,60	4,30	225	6,00	0,69	0,82000	24,60	30	NA13005100Q
60	68,40	4,20	270	6,00	0,69	1,10000	33,00	30	NA13006000Q
65	73,60	5,20	293	5,00	0,69	1,16500	34,95	30	NA13006500Q
70	79,00	4,80	316	5,00	0,69	1,24000	37,20	30	NA13007000Q
75	84,60	4,80	338	4,00	0,69	1,30000	39,00	30	NA13007500Q
102	114,60	6,30	459	3,00	0,69	2,24000	44,80	20	NA13010200N

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 24.11.2026