

FLEX ANT

Flexible PVC hose reinforced with an shock-resistant hard PVC spiral and copper wire for grounding

Applications	pellet transport, granulate conveying, furniture production, extraction systems, dosing
Structure	PVC, uncolored, transparent, plastic spiral / rigid PVC, coated strand / copper strand
Temperature	-5°C up to 60°C
Properties	good flexibility, smooth inside, corrugated outside, good chemical resistance, with copper wire for grounding, phthalate-free



hydrolysis
resistant



microbe-
resistant



grounding
wire



very smooth
inside



solids

**made
in
Germany**

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
38	46,00	4,00	190	6,00	0,59	0,58000	14,50	25	NA11103800P
38	46,00	4,00	190	6,00	0,59	0,58000	29,00	50	NA11103800R
40	48,00	4,00	200	6,00	0,90	0,60000	30,00	50	NA11104000R
50	58,60	4,00	250	5,00	6,00	0,78000	39,00	50	NA11105000R
50,5	59,60	4,00	250	5,00	0,90	0,78000	19,50	25	NA11105000P
70	79,00	4,50	350	4,00	0,90	1,33000	39,90	30	NA11107000Q