S 3 PVC S NOIR

Very flexible and light weight PVC hose with shock-resistant hard PVC spiral

Applications pond technology, water drain, irrigation, waste water, filter systems

Structure soft PVC, black, opaque, plastic spiral / rigid PVC

Temperature -5°C up to 60°C

Properties very good flexibility, corrugated outside, smooth inside, , good ozone- & UV-resistance



hydrolysis resistant · microbe-resistant · liquids

made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	23,80	2,40	19	0,39	0,11000	3,60	30	ND39301950Q
25	30,00	2,50	25	0,39	0,13000	5,40	30	ND39302550Q
32	38,00	3,00	32	0,34	0,20500	6,60	30	ND39303250Q
38	44,40	3,20	38	0,29	0,26000	8,10	30	ND39303850Q
40	46,40	3,20	40	0,29	0,27000	8,40	30	ND39304050Q
50	57,00	3,50	50	0,29	0,43500	12,60	30	ND39305050Q

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 25.11.2026