MONOFLEX RIGIDE

PVC hose reinforced with an impact-resistant rigid PVC spiral



Applications	liquid manure spreading, agriculture, irrigation, waste water, trailing hose application
Structure	soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-25°C up to 60°C
Properties	very robust & resistant, reinforced with shock-resistant PVC spiral, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
40	48,40	4,20	4,00	0,59	0,63000	0,43	0,6	NA100040060X00600
40	48,40	4,20	4,00	0,59	0,63000	0,57	0,8	NA100040060X00800
40	48,40	4,20	4,00	0,59	0,63000	0,71	1,00	NA100040060X01000

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026