


SMOOTHFLEXX PU FOOD X-TRA

- Applications** conveying technology, beverage production & conveying, grain conveying, food production & -conveying, medical devices
- Structure** TPU / Polyether-Polyurethane, transparent, plastic spiral / rigid PVC
- Temperature** -40°C up to 80°C
- Norms** certified according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C, D1, D2, E



| Inner Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|--------------------------|-------------------|---------------|------------|----------------|
| 38 | 0,80 | 133 | 2,00 | 0,30 | 0,34300 | 20 | ND35303800N |
| 51 | 1,00 | 179 | 1,50 | 0,25 | 0,50400 | 20 | ND35305100N |
| 63 | 1,00 | 221 | 1,50 | 0,25 | 0,63000 | 20 | ND35306300N |
| 76 | 1,00 | 266 | 1,50 | 0,25 | 0,74200 | 20 | ND35307600N |
| 102 | 1,00 | 357 | 1,30 | 0,22 | 0,99300 | 20 | ND35310200N |
| 127 | 1,00 | 445 | 1,30 | 0,20 | 1,23600 | 20 | ND35312700N |
| 152 | 1,00 | 532 | 1,00 | 0,16 | 1,47900 | 20 | ND35315200N |
| 203 | 1,20 | 711 | 0,70 | 0,10 | 1,97500 | 10 | ND35320300K |