FLEXX PU 1,4 STREET

Heavy weight and flexible Polyurethane hose



Applications	waste disposal vehicles, sweepers, municipal services, street cleaning, conveying of rubble
Structure	Polyether-Polyurethane, transparent, steel wire / spring steel wire / not coated / copper plated
Temperature	-40°C up to 100°C, short term up to 125°C
Properties	good flexibility, very good low-temperature flexibility, very good abrasion resistance, hydrolysis & microbe resistant, good oil & petrol resistance





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
180	191,00	1,40	216	0,35	0,25	27,01	10	ND55918000K
200	211,00	1,40	240	0,30	0,20	33,60	10	ND55920000K
203	214,00	1,40	245	0,30	0,20	0,00	10	ND55920300K

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026