

## MONOFLEXX SL VERT/NOIR

Flexible PVC hose reinforced with shock resistant rigid PVC spiral

<b>Applications</b>	agriculture, pond technology, waste water, irrigation, sewage treatment plants
<b>Structure</b>	PVC / soft PVC, green, transparent, plastic spiral / rigid PVC
<b>Temperature</b>	-5°C up to 60°C
<b>Properties</b>	good flexibility, high pressure resistance, high vacuum resistance, very smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
20	25,40	2,70	104	7,00	0,69	0,21000	10,50	50	NA90202065R
25	29,80	2,50	130	7,00	0,69	0,30000	6,25	25	NA90202565P
25	29,80	2,90	130	7,00	0,69	0,30000	12,50	50	NA90202565R
32	38,00	3,00	155	7,00	0,69	0,39000	9,75	25	NA90203265P
32	38,00	3,00	155	7,00	0,69	0,39000	19,50	50	NA90203265R
38	45,00	3,50	180	6,00	0,69	0,47000	13,00	25	NA90203865P
38	45,00	3,50	180	6,00	0,69	0,47000	23,50	50	NA90203865R
50	57,60	4,20	240	5,00	0,69	0,76000	19,00	25	NA90205065P
50	57,60	4,20	240	5,00	0,69	0,76000	38,00	50	NA90205065R