

GERTRESS 20 BARS

Flexible, multi-layer PVC hose with high-tensile polyester yarn reinforcement

Applications	compressed air, agricultural technology, construction machines, vehicle construction, compressors
Structure	PVC / soft PVC, black, opaque, cross braid
Temperature	-20°C up to 65°C
Properties	, high pressure resistance, , good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,40	3,20	24	20,00	60,00	0,12300	6,15	50	NS40000600R
6	12,40	3,20	24	20,00	60,00	0,12300	12,30	100	NS40000600T
9	15,40	3,20	36	20,00	60,00	0,19000	9,50	50	NS40000900R
9	15,40	3,20	36	20,00	60,00	0,15000	15,00	100	NS40000900T
10	16,40	3,20	40	20,00	60,00	0,16250	16,25	100	NS40001000T
13	21,00	4,00	52	20,00	60,00	0,26200	13,10	50	NS40001300R
13	21,00	4,00	52	20,00	60,00	0,26200	26,20	100	NS40001300T
16	25,60	4,80	64	20,00	60,00	0,41200	20,60	50	NS40001600R
19	28,60	4,80	76	20,00	60,00	0,43940	21,97	50	NS40001900R