S 7 HYP-TEF EL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive



Applications	paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, air extraction
Structure	Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / multi-layer
Temperature	-40°C up to 175°C, short term up to 190°C
Properties	light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive
Norms	TRBS 2153, ATEX 2014/34/EU





made in Germany

Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
102	60	0,51	0,10	3,75	6	ND76210200G
127	75	0,33	0,06	4,80	6	ND76212700G
152	90	0,22	0,04	5,40	6	ND76215200G
152	90	0,22	0,04	2,70	3	ND76215200B

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026