Smartflex SMT Comfort Premium

5-layer garden hose with innovative SMT fabric

Applications irrigation

Structure soft PVC, grey, opaque, SMT knitting

Temperature -20°C up to 65°C

Properties excellent flexibility, good tensile strength, crush-resistant, can be driven over, anti-torsion, kink-resistant, high pressure resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, rot proof, phthalate-free







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
15	20,80	2,90	90	12,00	36,00	0,20000	20,00	100	NS75001600T
25	33,20	4,10	125	7,00	21,00	0,43000	21,50	50	NS75002500R
25	32,80	3,90	125	7,00	21,00	0,43000	43,00	100	NS75002500T

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026