SOLIDFLEXX PU

Very heavy weight spiral hose made of PVC with highly abrasion resistant PU inner layer

Applications roof graveling, conveying of rubble, gravel conveying, sandblasting, conveying of abrasive media

Structure PVC, red, opaque, plastic spiral / rigid PVC

Temperature -20°C up to 60°C

Properties excellent abrasion resistance, high vacuum resistance, crush-resistant, very smooth inside, corrugated outside, with highly abrasion-resistant polyurethane inner layer, smooth, to ensure very low pressure losses, good mechanical strength







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
127	147,00	10,00	826	3,00	10,00	0,88	4,30000	129,00	30	NA13312700Q

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026