

AQUALIFE KTW TPE

TPE drinking water hose, multi-layered

| | |
|---------------------|---|
| Applications | drinking water, beverage production & conveying |
| Structure | TPE/E, blue, opaque, cross braid |
| Temperature | -30°C up to 70°C, short term up to 90°C |
| Properties | hydrolysis & microbe resistant, weather proof, high pressure resistance, crush-resistant, smooth inside, smooth outside |
| Norms | DVGW W 270 |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Burst Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|----------------------|---------------|-----------------------------|------------|----------------|
| 10 | 15,40 | 2,50 | 70 | 14,00 | 42,00 | 0,09000 | 2,25 | 25 | NS61101000P |
| 10 | 15,40 | 2,50 | 70 | 14,00 | 42,00 | 0,09000 | 4,50 | 50 | NS61101000R |
| 13 | 18,80 | 3,00 | 70 | 15,00 | 45,00 | 0,14120 | 3,53 | 25 | NS61101300P |
| 13 | 18,80 | 3,00 | 70 | 15,00 | 45,00 | 0,14100 | 7,05 | 50 | NS61101300R |
| 19 | 26,60 | 4,10 | 130 | 15,00 | 45,00 | 0,23200 | 5,80 | 25 | NS61101900P |
| 19 | 27,20 | 4,10 | 130 | 15,00 | 45,00 | 0,23200 | 11,60 | 50 | NS61101900R |
| 25 | 34,60 | 4,80 | 220 | 10,00 | 30,00 | 0,40720 | 10,18 | 25 | NS61102500P |
| 25 | 34,60 | 4,80 | 220 | 10,00 | 30,00 | 0,40700 | 20,35 | 50 | NS61102500R |