GERTRESS 40 BARS

Multilayer PVC pressure hose with highly tear-resistant Polyester fabric

Applications sprayers, agriculture, compressed air, construction machines, fertilizer spreading

Structure soft PVC, blue, opaque, cross braid

Temperature -10°C up to 60°C

Properties very good flexibility, very high pressure resistance, very good chemical resistance, good resistance to compressed air containing mineral oil, good ozone- & UV-resistance, weather proof







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
9	16,00	3,50	40,00	120,00	0,18000	18,00	100	NS20000900T
9	16,00	3,50	40,00	120,00	0,18000	9,00	50	NS20000900R
10	17,00	3,50	40,00	120,00	0,19000	19,00	100	NS20001000T
10	17,00	3,50	40,00	120,00	0,19000	9,50	50	NS20001000T
13	21,00	4,00	40,00	120,00	0,28000	28,00	100	NS20001300T
13	21,00	4,00	40,00	120,00	0,28000	14,00	50	NS20001300R
16	25,60	4,00	40,00	120,00	0,36500	18,25	50	NS20001600R
19	28,60	4,80	40,00	120,00	0,42500	21,25	50	NS20001900R
25	35,00	5,00	40,00	120,00	0,59500	29,75	50	NS20002500R

Ocono France SARL | 30 Chemin de Fortuneau | 26200 Montélimar | France | T +33 475 017575 | france@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026